

FLEX-SERIES

HPS Standard Portable Stretch Wrapper

Durability, Reliability & Performance

Features

- 4-Point caster support
- Password protected HMI settings
- 12 RPM variable speed with "soft-start"
- 260% powered film pre-stretch
- Forklift portable from front & rear
- AC/VFD motors reduce maintenance
- Easy load carriage



FLEX-SERIES

HPS Standard Portable Stretch Wrapper

Precision Engineering

is ideal for those customers who...

- Need a higher level of durability than an entry-level turntable machine.
- Want the ability to quickly relocate the machine.
- Want to wrap loads weighing up to 4,000 lbs.

Insta-Thread Film Delivery System



Insta-Thread™ with standard pre-stretch rate of 260% not only helps reduce film costs on every load you wrap, but the film on the load will be stronger, so loads are more secure.

Robust Two Chain Drive System

The Flex HPS features the Insta-Thread™ film carriage which is driven by a strong and robust 2 chain drive system for smooth, reliable operation.



Functional Control Panel



Featuring a simple yet functional control panel with physical start and e-stop button and a menu driven touch panel for setting operating parameters and other functions.

Features

- 12 RPM Variable Speed Turntable with "soft-start"
- 4,000 lb Maximum Load Capacity
- Economical 260% Powered Film Pre-Stretch
- 4-Point Caster Support for Reliable Operation
- Password Protected HMI Settings
- Automatic Load Height Photoeye
- AC/VFD Motors Reduce Maintenance
- Forklift Portable from Front or Rear

Options

- Tower Extension to Wrap up to 110"
- Weigh Scale Package
- 8 Point Caster Support

Technical Data

- Machine Dimensions: 96"L x 48"W x 99"H
- Standard Load Size: 55"L x 55"W x 80"H
- Maximum Load Weight: 4,000 lbs
- Powered Film Pre-Stretch: 260%
- Power Supply: 115V, Single Phase, 20A, 60HZ

Standard Dimensions

