

MA-SERIES

MA-DX Deluxe Automatic Rotary Wrapper

High Speed Reliability

Features

- 4,500 lb max. capacity
- 18 RPM counter-balanced rotary arm
- 23" precision ring bearing
- 260% powered film pre-stretch
- AB micrologix PLC controller
- AC variable frequency drive



MA-SERIES

MA-DX Deluxe Automatic Rotary Wrapper

Precision Engineering

is ideal for those customers who...

- Have very high productivity/throughput requirements.
- Have light or unstable loads.
- Want to wrap loads weighing up to 4,500lbs.

Durable Tower Drive System



The MA-DX features a durable chain and sprocket tower drive system with a precision ring bearing to provide for durable and reliable operation. The dry-lube chain requires little maintenance as compared to direct drive "tooth to tooth" direct gear drives which require constant greasing.

Film Tail Treatment System

The new film tail treatment system features an innovative asymmetrical film clamp that grips the film while the impulse hot wire cuts the film. Then, the load-seeking pneumatically actuated brush smooths and secures the film tail to the side of the load.



High Quality Conveyor System



High quality conveyor sections are pre-wired, conduit photocells and guards. Conveniently located junction boxes and connectors make trouble-shooting fast and easy.

Features

- Fully Enclosed Slip Ring Assembly
- 4 Leg Reinforced Heavy Duty Frame
- 18 RPM Counter-Balanced Rotary Arm
- AB MicroLogix PLC Controller
- 23" Precision Ring Bearing
- AC Variable Frequency Drive
- Automatically Adjusts for Various Load Heights

Options

- 6,000 lb Load Capacity
- 110" Load Height
- 30" Insta-Thread Film Carriage

Technical Data

- Machine Dimensions: 293"L x 131"W x 134"H
- Maximum Load Size: 48"L x 48"W x 80"H
- Maximum Load Weight: 4,500 lbs
- Powered Film Pre-Stretch: 260%
- Power Supply: 480V, 3ph, 60hz