

MA-SERIES

MA-ST Standard Automatic Rotary Wrapper

Speed Affordable

Features

- 4,500 lb max. capacity
- 12 RPM rotary arm
- AB micrologix PLC controller
- 260% powered pre-stretch carriage
- Fully enclosed slip ring assembly
- AC variable frequency drive



MA-SERIES

MA-ST Standard Automatic Rotary Wrapper

Precision Engineering

is ideal for those customers who...

- Have high productivity/throughput requirements.
- Have light or unstable loads.
- Want to wrap loads weighing up to 4,500lbs.

Insta-Thread Film Delivery System



Insta-Thread™ with standard pre-stretch rate of 260% not only helps reduce film costs on every load you wrap, but the film on the load will be stronger, so loads are more secure

Film Treatment Tail System

The new film tail treatment system features an innovative asymmetrical film clamp that grips the film while the impulse hot wire cuts the film. Then, the load-seeking pneumatically actuated brush smooths and secures the film tail to the side of the load.



Sprocket Drive System



The MA-ST features a durable chain and sprocket tower drive system with a precision ring bearing to provide for durable and reliable operation. The dry-lube chain requires little maintenance as compared to direct drive "tooth to tooth" direct gear drives which require constant greasing.

Features

- Full Enclosed Slip Ring Assembly
- Single Leg or 2 Leg Gantry frame
- 12 RPM Rotary Arm
- AB MicroLogix PLC Controller
- Precision Ring Bearing with ANSI Chain/Sprocket Drive
- AC Variable Frequency Drive
- Automatically Adjusts for Various Load Heights

Options

- 6,000 lb Load Capacity
- 110" Load Height
- 30" Insta-Thread Film Carriage

Technical Data

- Machine Dimensions: 293"L x 145"W x 130"H
- Maximum Load Size: 48"L x 48"W x 80"H
- Maximum Load Weight: 4,500 lbs
- Powered Film Pre-Stretch: 260%
- Power Supply: 480V, 3ph, 60hz