



Shown with optional exit table & casters.

# RSA 3036-SB

## Random Semi-Automatic Case Sealer

PPI's RSA Series Case Sealers are operator-fed machines that automatically adjust for each size case processed. A PPI random case sealer is your solution when production has a need for different sized cases to be processed through a single case sealer.

Every PPI case sealer comes with a HSD 2000-ET II tape head with adaptive technology to provide optimal tape application and wipe down to each of the three taped panels of the case.

Specifically designed to process a larger range of cases, this oversized side belt drive random case sealer contains the same package of features and benefits as the standard sized RSA 2024-SB. Construction is reinforced to handle larger, heavier cases. Standard 4" tall drive bases provide twice the gripping power.

When you compare features, benefits and value, PPI Case Sealers are the right choice for operators, plant engineers, maintenance and purchasing.

### FEATURES & BENEFITS

- Heavy duty construction will process up to 85 lb cases with dual columns for maximum processing stability
- 4" tall drive bases standard
- 2 modes of operation
  - Upper head retained random mode
  - Bottom only seal mode
- Pneumatic in-feed gate assures proper positioning of the case during processing and drastically reduces jams
- Twin 1/3 HP high torque gear motors process larger, heavier cases
- Self-tensioning, self-tracking belt drive simplifies belt replacement
- Offset tape heads process cases as low as 5"
- Unique "Clear" push button to clear jams and replace bottom tape roll

These machines are engineered to provide:

- Industry leading features
- Heavy duty construction for 24/7 operation
- Ergonomic and user friendly operation

# RSA 3036-SB

Min Case (L x W x H)	Max Case (L x W x H)	Case Weight	Belt Speed	Electric	Compressed Air Requirements	Tape Width	Conveyor Height	Machine Weight	Machine Dimensions (L x W x H)
6" x 5¼" x 5"	Inf x 30" x 36"	0 - 85 lbs	82 ft/min	110v., 1ph., 60hz., 6A., (2 x ½ HP)	9 CFM @ 90 PSI	48 - 72 mm (2" - 3")	24" - 30"	816 lbs crated	44½" x 47½" x 83"

Tip up top tape head simplifies roll replacement



Digital pneumatics to improve throughput speed



Optional random top squeezers compress major flaps



Standard 4" tall side belts



"Clear" button for jams & replacing bottom tape roll




Self-tensioning & self-tracking drive belts simplify belt replacement



Twin ½ HP gear motors to process up to 85 lb cases



Index gate positions case for proper processing



Selectable top & bottom or bottom only modes



Offset 3" wide tape heads process cases as low as 5"



## OPTIONS & ACCESSORIES



Swivel & locking casters  
(Shown above)



Tape head spare parts kit



Optional in-feed and exit tables  
(Shown above)