

FLEX-SERIES

LPA Automatic Portable Stretch Wrapper

Durability, Reliability & Performance

Features

- 5,000 lb max. capacity
- 15 RPM variable speed with "soft-start"
- 260% powered film pre-stretch
- Forklift portable from front & rear
- AC/VFD motors reduce maintenance



FLEX-SERIES

LPA Automatic Portable Stretch Wrapper

Precision Engineering

is ideal for those customers who...

- Use a mix of pump trucks, walkies and fork lifts.
- Need a higher level of durability than an entry-level turntable machine.
- Want to reduce/eliminate the need for operators to leave their vehicle.
- Need more productivity but can't justify an expensive automated system.
- Want to wrap loads weighing up to 5,000 lbs

Insta-Thread Film Delivery System



All Flex LPA's are equipped with the Insta-Thread™ film delivery system and film tail treatment mechanism with drop-in film loading for fast, easy and safe threading of film.

DuraGlide Precision Ring Bearing

The Flex LPA features a precision ring bearing and the DuraGlide cams that provide reliable support for loads weighing up to 5,000 lbs



Versatile HMI Control Panel



A versatile HMI control panel with touch screen display guides users through a range of menu items for easy adjustment of operating parameters. Settings can be password protected for added security.

Features

- 15 RPM Variable Speed with "soft-start"
- Economical 260% Powered Film Pre-Stretch
- 63" Diameter Turntable for Loads up to 50"x50"
- Full Surround Deck Protects Turntable
- DuraGlide Support Bearing
- AC/VFD Motors Reduce Maintenance
- Forklift Portable from Front or Rear

Options

- Loading Ramp
- Weigh Scale Package
- 6,000 lb Turntable Capacity Upgrade
- 30" Insta-Thread Film Carriage

Technical Data

- Standard Dimensions: 100"L x 68"W x 89"H
- Standard Load Size: 50"L x 50"W x 80"H
- Standard Load Weight: 5,000 lbs
- Powered Film Pre-Stretch: 260%
- Power Supply: 110V Single Phase

Standard Dimensions

